

## **AXIS T8342 Door/Window Sensor**

Wireless door/window sensor

AXIS T8342 Door/Window Sensor enables the triggering of events such as notification messages, illumination, and much more, when the door or window is opened. By communicating wirelessly with AXIS M5065 PTZ Network Camera or connected Z-Wave Plus® controllers, the door/window sensor can be used in small security solutions with less cabling. The wireless I/O connectivity also enables flexible installation as the sensor can easily be mounted on a door, window, or cabinet according to your needs.

- > Wireless I/O connectivity
- > Z-Wave Plus® compatibility
- > S2 security compliant
- > Battery included





www.cxis.com T10116878/EN/M3.2/2010

## AXIS T8342 Door/Window Sensor

Supported products	AXIS M5065 PTZ Network Camera Compatible with other Z-Wave Plus® control devices
Network	
Supported protocols	Z-Wave Plus®. For more information on the supported command classes, see the product's User Manual
General	
Casing	Plastic Color: white
Sustainability	PVC-free
Power	2 x CR2450 3.0 V Lithium battery Battery life: 1 year <sup>a</sup>
Distance	Transmitting range up to 100 meters (328 ft)
Frequency	908.42 MHz (US), 922.5 MHz (JP), 868.42 MHz (EU)
Operating conditions	-10 °C to 40 °C (14 °F to 104 °F)
Storage conditions	-20 °C to 60 °C (-4 °F to 140 °F)

	Approvals	EMC FCC Part 15 Subpart C, ICES-003 Class B, VCCI Class B, EN 301 489-1 V2.1.1, EN 301 489-13 V2.1.1 Radio EN 300 220-2 v3.1.1, EN 300 220-2 V3.1.1
	Dimensions	Sensor: 31 x 15 x 70 mm (1.22 x 0.59 x 2.76 in) Magnet: 11 x 15 x 70 mm (0.43 x 0.59 x 2.76 in)
	Weight	38 g (0.08 lbs)
	Included accessories	Installation guide, mounting kit, 2 x CR2450 3.0 V Lithium battery
	Warranty	3-year warranty, see axis.com/warranty

a. Measured at 10 triggers per day.

Environmental responsibility: axis.com/environmental-responsibility

