

# AXIS FA51 Main Unit

## Single-channel main unit with HDMI output

This modular single-channel main unit can connect to one sensor unit offering highly discreet surveillance. Featuring an HDMI output, it's possible to display live video on a public viewing monitor. And, AXIS Face Detector highlights faces within bounding boxes to let would-be shoplifters know they're being monitored and proactively reduce shoplifting. Compatible with all AXIS FA sensor units including IR sensor units, you'll enjoy excellent video quality even in complete darkness. Furthermore, Axis Edge Vault protects your Axis device ID and simplifies authorization of Axis devices on your network.

- > **HDTV 1080p at full frame rate**
- > **AXIS Face Detector preinstalled**
- > **HDMI output for public viewing monitors**
- > **1 configurable input/output port**
- > **Compatible with all AXIS FA sensor units**



# AXIS FA51 Main Unit

<b>System on chip (SoC)</b>		AXIS People Counter, autotracking Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="https://axis.com/acap">axis.com/acap</a>
<b>Model</b>	ARTPEC-6	
<b>Memory</b>	1024 MB RAM, 512 MB Flash	
<b>Video</b>		<b>General</b>
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	<b>Casing</b>
<b>Resolution</b>	1920x1080 (1080p) to 160x90	IP4X- Aluminum casing Color: black NCS S 9000-N
<b>Wide dynamic range</b>	Forensic WDR	<b>Sustainability</b>
<b>Frame rate</b>	Up to 25/30 fps in all resolutions	PVC free, BFR/CFR free
<b>Video streaming</b>	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/ABR/MBR H.264 HDMI	<b>Power</b>
<b>HDMI output</b>	Single camera source Playlist: single camera sources, still images 1080p 30/25/24 fps (50/60 Hz) 720p 50/60 fps (50/60 Hz) 576p 50 fps (50/60 Hz) 480p 60 fps (50/60 Hz)	<b>Connectors</b>
<b>Image settings</b>	Contrast, brightness, sharpness, white balance, exposure control, exposure zones, compression, rotation: 0°, 90°, 180°, 270° including corridor format, mirroring, polygon privacy mask, control queue	RJ45 10BASE-T/100BASE-TX PoE RJ12 for sensor unit 4-pin terminal block for two configurable alarm inputs/outputs (12 V DC output, max. load 50 mA) HDMI type D
<b>Pan/Tilt/Zoom</b>	Digital PTZ, preset positions	<b>Storage</b>
<b>Network</b>		Support for microSD/microSDHC/microSDXC card and encryption Recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="https://axis.com">axis.com</a>
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1x (EAP-TLS) <sup>a</sup> network access control, digest authentication, multi-level user, brute force delay protection, signed firmware, secure boot, Axis Edge Vault, Axis device ID, secure keystore (CC EAL4 certified)	<b>Operating conditions</b>
<b>Supported protocols</b>	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS <sup>a</sup> , TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP <sup>®</sup> , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, RTSP, RTP, SRTP, TCP, RTCP, DHCP, SOCKS, SSH, CDP, MQTT, Syslog, Link-Local address (ZeroConf)	-20 °C to 50 °C (-4 °F to 122 °F) Maximum temperature (intermittent): 60 °C (140 °F) Start-up temperature: -20 °C (-4 °F) Humidity 10–85% RH (non-condensing)
<b>System integration</b>		<b>Storage conditions</b>
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="https://axis.com">axis.com</a> One-click cloud connection ONVIF <sup>®</sup> Profile G, ONVIF <sup>®</sup> Profile M, ONVIF <sup>®</sup> Profile S, and ONVIF <sup>®</sup> Profile T, specification at <a href="https://onvif.org">onvif.org</a>	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 10–85% RH (non-condensing)
<b>Event conditions</b>	Device status, edge storage, I/O, PTZ, scheduled event, video MQTT subscribe	<b>Approvals</b>
<b>Event actions</b>	Toggle I/O, send images, publish MQTT, send notifications, overlay text, recordings, SNMP trap messages, status LED, video clips MQTT publish	EMC EN 55035, EN 55032 Class A, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety IEC/EN/UL 62368-1, CAN/CSA C22.2 No. 62368-1, IS 13252 Environment IEC/EN 60529 IP4X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78 Network NIST SP500-267
<b>Data streaming</b>	Event data	<b>Dimensions</b>
<b>Analytics</b>		24 x 49 x 152 mm (0.9 x 1.9 x 6.0 in)
<b>Applications</b>	Included AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard AXIS Video Motion Detection, AXIS Face Detector, active tampering alarm Supported	<b>Weight</b>
		195 g (0.43 lb)
		<b>Included accessories</b>
		Installation guide, Windows <sup>®</sup> decoder 1-user license, terminal block connector
		<b>Optional accessories</b>
		AXIS T8415 Wireless Installation Tool, AXIS Surveillance Cards, AXIS T8120 Midspan 15 W 1-port For more accessories, see <a href="https://axis.com">axis.com</a>
		<b>Video management software</b>
		AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at <a href="https://axis.com/vms">axis.com/vms</a>
		<b>Languages</b>
		English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese
		<b>Warranty</b>
		5-year warranty, see <a href="https://axis.com/warranty">axis.com/warranty</a>
		a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. ( <a href="https://openssl.org">openssl.org</a> ), and cryptographic software written by Eric Young ( <a href="mailto:ey@cryptsoft.com">ey@cryptsoft.com</a> ).
		Environmental responsibility: <a href="https://axis.com/environmental-responsibility">axis.com/environmental-responsibility</a>